

MATERIAL SAFETY DATA SHEET

C.A.T. Products, Inc.
103 Gypsum Rd.
Stroudsburg, Pa 18360
(570) 402-1154
(800) 424-9300 - Chemtrec

*May be used to comply with OSHA's
Hazard Communication Standard
29CFR 1910.1200. Standard
must be consulted for specific
requirements*

SECTION I - IDENTIFICATION

Trade Name: Diesel Induction System Cleaner
Product Code: CP-SL375C
Part #: 1003
U.S. D.O.T. Shipping Name: Combustible liquid, n.o.s.
Technical Name: Not Applicable
U.S. D.O.T. Primary Hazard Class: Non Regulated
IATA (Airline): Non Regulated
Maritime: Non Regulated
U.S. D.O.T. Secondary Hazard Class: Not Applicable
Identification Number: NA1993
Packing Group: Not Applicable

SECTION II - HAZARDOUS INGREDIENTS--IDENTITY INFORMATION

<u>Hazardous Components</u>	<u>CAS #</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Aliphatic naphtha	64742-88-7	100 ppm	100 ppm
Petroleum Distillate	64742-65-0	NA	NA

Other components are considered to be non-hazardous as per OSHA 29 CFR 1910.1200.
Primary Component is considered to be non hazardous - PEA

HMIS rating Health - 2, Flammability - 1, Reactivity - 0, PPE to be determined at work site.

SECTION III - PHYSICAL & CHEMICAL CHARACTERISTICS

Flash Point: >142°F ASTM D56 Tag Closed Cup
Specific Gravity (H₂O=1): 0.877 @ 25°C
Vapor Density (Air=1): 4.6
Evaporation Rate (BA=1): >0.1
% Solids: 0
Weight (lb./gal.): 7.32
Appearance & Odor: Clear green liquid, solvent odor

SECTION IV - FIRE & EXPLOSION HAZARD DATA

Extinguishing Media: Regular foam, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Wear a Self Contained Breathing Apparatus with full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Material will float on water.
Unusual Fire & Explosion Hazards: Toxic fumes, gases, or vapors may evolve on burning. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames, and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

SECTION V - REACTIVITY DATA

Stability: Stable.
Materials to Avoid: Nitric acid, Sulfuric acid, strong oxidizing products.
Conditions to Avoid: Contact with open flame.
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide and unidentified organic compounds may be formed during combustion.
Hazardous Polymerization: Will not occur.

SECTION VI

HEALTH HAZARD DATA

SIGNS AND SYMPTOMS OF EXPOSURE:

Eyes:	Irritation, redness, stinging.
Dermal:	Dryness, irritation, redness.
Inhalation:	Vapors may irritate nose, throat, and respiratory tract.
Ingestion:	Nausea, vomiting, dizziness, headache, blurred vision.

EMERGENCY RESPONSE AND FIRST AID PROCEDURES:

Eyes:	If symptoms develop, move individual away from exposure and into fresh air. Flush eyelids with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, get medical attention.
Dermal:	Wash with soap and water and then flush with water until all chemical is removed. Remove contaminated clothing promptly and wash before reuse. If irritation persists get medical attention.
Inhalation:	Remove to fresh air. If breathing has stopped, give artificial respiration, provided a qualified individual is available. If breathing is difficult, give oxygen, provided a qualified operator is available. Get prompt medical attention.
Ingestion:	If conscious, Do Not induce vomiting. This material is an aspiration hazard. Drink large amounts of water. Get medical attention. If vomiting occurs, give additional water. If drowsy or unconscious, place on left side with head down. Take immediately to hospital. Do Not attempt to induce vomiting or give by mouth to an unconscious person. If possible, do not leave individual unattended.
anything	

SECTION VII - TOXICOLOGICAL INFORMATION

ACUTE HEALTH HAZARDS:

Eyes:	Mild eye irritation, may cause moderate corneal injury and effects may be slow to heal.
Dermal:	Exposure may cause skin irritation. Prolonged or repeated exposure may cause drying, redness, and cracking of the skin. Skin absorption is possible but harmful effects are not expected from this route of exposure under normal conditions of handling and use.
Inhalation:	Short term toxicity from inhalation of mists and vapors is low. Breathing small amounts during normal handling is not likely to cause harmful effects; breathing large amounts may be harmful to nose, throat, respiratory tract, and central nervous system.
Ingestion:	Harmful or fatal if swallowed. Pulmonary aspiration hazard if swallowed and/or vomiting occurs - can enter lungs and cause damage.

CHRONIC HEALTH HAZARDS:

None expected at the industrial level.

Pre-existing medical conditions aggravated by exposure:

Disorders or diseases of the skin, eye, liver, kidney, nervous system, respiratory and/or pulmonary system, lung (e.g. - Asthma-like conditions).

SECTION VIII

SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Dike or pill area. Remove all sources of ignition. Ventilate area if necessary. Absorb free liquid with earth, sand, clay, or absorbent pads and place in non-leak containers for disposal. Flush area for trace residue and dispose of as below. Wear respiratory protection for large spill, leak or release. Use personal protective equipment as stated in Section IX. Do not flush to drain/storm sewer.

WASTE DISPOSAL METHOD:

In accordance with Local, State and Federal Laws.

SECTION IX - SPECIAL PROTECTION INFORMATION

Respiratory Protection:	Normally not needed in a well ventilated area. If workplace exposure limit(s) of product or any component is exceeded (see exposure guidelines), a NIOSH approved air supplied respirator is advised.
Ventilation:	Mechanical to maintain exposure below TLV(s).
Protective Gloves:	Rubber.
Eye Protection:	Goggles or safety glasses. Provide eye wash station and washing facilities near use or handling facilities.
Other:	Wear full work clothing needed to minimize exposure.
Hygienic Practices:	Always wash face and hands after contact. Remove contaminated clothing and wash before reuse.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in the use of this material.

Revision Date 02/19/12