SAFETY DATA SHEET

SECTION I: IDENTIFICATION

C.A.T. Products, Inc.

May be used to comply with OSHA's

103 Gypsum Rd

Stroudsburg, PA 18360

(800) 872-8921

May be used to comply with OSHA's

Hazard Communication Standard

29CFR 1910.1200. Standard

must be consulted for specific

24 hr. emergency phone ChemTel 1-800-255-3924 requirements..

Trade Name: 6011 Power Steering Fluid

Product Code: CP-SL391 Not Applicable U.S. D.O.T. Shipping Name: Technical Name: Not Applicable Non Regulated U.S. D.O.T. Primary Hazard Class: U.S. D.O.T. Secondary Hazard Class: Not Applicable Not Applicable Identification Number: IATA (Airline) Non Regulated Maritime Non Regulated

Packing Group:

Product type & use: Consumer (retail) product, Power Steering additive

SECTION II: HAZARDS IDENTIFICATION

GHS signal word: GHS pictogram: Precautionary statement:

Warning Keep out of reach of children

SECTION III: COMPOSTITION INFORMATION ON INGREDIENTS

Ingredients cas no range % Dibutyl phosphonate 1809-19-4 0.01-0.10 Alkylated phenol confidential 0.01-0.1 Carboxylate acid ester confidential 0.01-0.1 0.001-0.02 Toluene 108-88-3 Diphenylamine 122-39-4 0.001-0.02

SECTION IV: FIRST-AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

Eyes: Flush with large amounts of water for 15 minutes.

Dermal: Wash with soap and water. Inhalation: Remove victim to fresh air.

Ingestion: Do not induce vomiting. Get medical attention or call poison control.

SECTION V: FIRE-FIGHTING MEASURES

Extinguishing Media: Dry chemical foam, or water fog.

Special Fire Fighting Procedures: Protect against decomposition products. Wear Self Contained Breathing

Apparatus.

Unusual Fire & Explosion Hazards: Heating of non-vented container may cause explosion. Keep

surrounding containers cool with water spray

Stability: Stable.

Conditions to Avoid: Contact with open flame.

Hazardous Decomposition Products: Carbon Monoxide and unidentified organic compounds may be formed

during combustion.

Hazardous Polymerization: Will not occur.

SECTION VI: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Dike area. Remove all sources of ignition. Ventilate area if necessary. Absorb free liquid with earth,

CAT Power Steering Fluid Page 1 of 3

sand, clay, or absorbent pads and place in non-leak containers for disposal. Flush area for trace residue and dispose of as below.

WASTE DISPOSAL METHOD:

In accordance with Federal, State, and Local Laws.

SECTION VII: HANDLING AND STORAGE

Protect against physical damage. Store in a cool, dry, well-ventilated location away from any area where fire hazards may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid sparks. Storage and use areas should be NO SMOKING areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapor, liquid); observe all warnings listed for the product. Do not attempt to clean empty containers since residue is difficult to remove. DO not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, sparks, flame, static electricity, or other sources of ignition: they may explode and cause injury or death.

SECTION VIII: SPECIAL PROTECTION INFORMATION

Respiratory Protection: Normally not needed in a well-ventilated area.

Ventilation: Mechanical to maintain good airflow.

Protective Gloves: Rubber.

Eye Protection: Goggles or safety glasses.

Other: As needed to minimize exposure.

Hygienic Practices: Always wash face and hands after contact.

SECTION IX: TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Flash Point: >200 °F ASTM D56 Tag Closed Cup

Boiling Point: not available Specific Gravity (H₂O=1): 0.855 @ 25°C

Solubility in Water: nil Viscosity cps @ 25°C 50cps

Appearance & Odor: clear, orange liquid, petroleum odor

Note: Not all tests are conducted routinely. It is recommended that you conduct your own tests.

SECTION X; STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Contact with open flame.

Hazardous Decomposition Products: Carbon Monoxide and unidentified organic compounds may be formed

during combustion.

Hazardous Polymerization: Will not occur.

SECTION XI: TOXICOLOGICAL INFORMATION

SIGNS AND SYMPTOMS OF EXPOSURE:

Eyes: Irritation, redness.

Dermal: Dryness, irritation, redness.

Inhalation: Vapors may irritate nose, throat, or respiratory tract. Ingestion: Nausea, vomiting, dizziness, headache, blurred vision.

Acute Health Hazards: Irritation of skin and eyes.

Chronic Health Hazards: Observations in animals include blood, kidney and reproductive effects.

SECTION XII: ECOLOGICAL INFORMATION

No data not available at this time.

SECTION XIII: DISPOSAL CONSIDERATIONS

Whatever cannot be saved for recovery and recycling should be handled as hazardous waste and disposed of in accordance with State, Federal, and Local laws.

SECTION XIV: TRANSPORT INFORMATION

CAT Power Steering Fluid Page 2 of 3

SECTION XV: REGULATORY INFORMATION
IATA
IMDG
DOT
General Transportation Information
compliance.

NOTE: Information in this section (Section 14) is presented as a guide only. Requirements may vary depending upon package size and exceptions used, if any. Follow current, applicable requirements under DOT, TDG, IMO/IMDG, ICAO/IATA to ensure regulatory

This product requires a proposition 65 statement.

SECTION XVI: OTHER INFORMATION

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in the use of this material.

Issue date May 19, 2015
Revision date: ____/__/___

CAT Power Steering Fluid Page 3 of 3