

MATERIAL SAFETY DATA SHEET

C.A.T. Products, Inc.
103 Gypsum Rd.
Stroudsburg, Pa 18360
(570) 402-1154
(800) 424-9300 - Chemtrec

*May be used to comply with OSHA's
Hazard Communication Standard
29CFR 1910.1200. Standard
must be consulted for specific
requirements.*

Section I – Product Identification

Product Name: Trans Kleen Pre-Flush Cleaner
Part #: 2060
Chemical Family: Petroleum Formula: Proprietary
Product Code: CP-SL366
U.S. D.O.T. Shipping Name: Non Hazardous
Technical Name: Not Applicable
U.S. D.O.T. Primary Hazard Class: Non Regulated
U.S. D.O.T. Secondary Hazard Class: Not Applicable
Identification Number: Not Applicable
Packing Group: Not Applicable
Reportable Quantity: Not Applicable

Hazardous Material Description, Proper Shipping Name, Hazard Class, Hazard ID No.: None
Additional Hazard Classes (as applicable): May be used to comply with OSHA 29 CFR 1910-1200. Standard must be consulted for specific requirements.

Section II – Hazardous Ingredients/Identity Information

<u>Hazardous Components</u>	<u>CAS #</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Ethylene Glycol Monobutyl ether	111-76-2	5 ppm	25 ppm
Aliphatic Petroleum Distillates	64741-44-2	100 ppm	100 ppm
Proprietary component			

Other components are considered to be non-hazardous as per OSHA 29 CFR 1910.1200.

Section III – Physical & Chemical Data

Flash Point: Greater than 200 Degrees F
Specific Gravity (H₂O=1): 0.835
Vapor Density (Air=1): >4
Evaporation Rate (BA=1): <1
% Solids: 0
Weight (lb/gal): 6.97
Volatile Organic Compounds: % 0.49 lbs/gallon
Appearance And Odor: Light red liquid, petroleum, ether odor

Section IV – Fire & Explosion Hazard Data

Extinguishing Media: Regular foam, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Wear self contained breathing apparatus with full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Material will float on water.
Unusual Fire and Explosion Hazards: Toxic fumes, gases, or vapors may evolve on burning. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because even residue can ignite explosively.

Section V – Health Hazard Data

Effects of Overexposure: Conditions to Avoid. Slight eye and skin irritation
Threshold Limit Value Permissible: 5.00 mg/m³
Primary Routes of Entry: Inhalation x Skin Contact x Eye Contact Ingestion x
Emergency and First Aid Procedures: Move to well ventilated area, flush skin thoroughly with soap & water. If swallowed do not induce vomiting. Get medical attention. Wash skin with soap & water.

Section VI – Reactivity Data

Stability: Stable

Hazardous Polymerization: Will not occur

Incompatibility: Material to avoid. Strong Oxidizers

Page 1

Section VII – Spill or Leak Procedure

Steps To Be Taken In Case Material Is Released Or Spilled: Contain spill mop or absorb on fire retardent treated saw dust or other absorbent material, eliminate all ignition sources, ventilate area.

Waste Disposal Method: Dispose into regulatory disposal facilities in accordance with local and state laws.

Section VIII – Special Protection Information

Respiratory Protection: None, other than adequate ventilation

Ventilation: Adequate

Protective Gloves (specify type): Avoid skin contact-rubber gloves

Eye Protection (specify type): Safety glasses

Other Protective Equipment: None required

Section IX – Special Precautions

Precautions To Be Taken In Handling And Storing: Combustible liquid, keep away from fire, sparks and extreme heat.

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in the use of this material.

Revision Date 5/22/07

