

## SAFETY DATA SHEET

### SECTION I: IDENTIFICATION

C.A.T. Products, Inc.  
103 Gypsum Rd  
Stroudsburg, PA 18360  
(800) 872-8921  
24 hr. emergency phone ChemTel 1-800-255-3924

*May be used to comply with OSHA's  
Hazard Communication Standard 29CFR 1910.1200.  
Standard must be consulted for specific  
requirements.*

Trade Name: 1007 Fuel System Cleaner  
Product Code: CP-SL373  
Product Type & Use: Consumer (retail) Product, Fuel System Additive

### SECTION II: HAZARDS IDENTIFICATION

#### GHS Signal Word

Danger

#### GHS Pictograms



#### Precautionary Statements

Flammable liquid  
Harmful if swallowed  
Skin irritant  
Keep out of reach of children

### SECTION III: COMPOSITION/INFORMATION ON INGREDIENTS

<u>Ingredients</u>	<u>CAS Numbers</u>	<u>Range %</u>
Distillates, petroleum, hydrotreated light	64742-47-8	70-100
2-Butoxy ethanol	111-76-2	1-5
Solvent naphtha (petroleum), light aromatic	64742-95-6	1-5
Benzene, 1,2,4-trimethyl-	95-63-6	0.1-2
Benzene, 1,3,5-trimethyl-	108-67-8	0.1-2
N-Propylbenzene	103-65-1	0.01-0.99
Xylene	1330-20-7	0.01-0.99
Cumene	98-82-8	0.01-0.99
Benzene, 1,2,3-trimethyl	526-73-8	0.01-0.99

### SECTION IV: FIRST-AID MEASURES

#### EMERGENCY AND FIRST AID PROCEDURES:

Eyes: Flush with large amounts of water for 15 minutes.  
Dermal: Wash with soap and water.  
Inhalation: Remove victim to fresh air.  
Ingestion: Do not induce vomiting. Seek medical attention or call poison control.

### SECTION V: FIRE-FIGHTING MEASURES

Extinguishing Media: Dry chemical foam, or water fog.  
Special Fire Fighting Procedures: Protect against decomposition products. Wear Self-Contained Breathing Apparatus.  
Unusual Fire & Explosion Hazards: Heating of non-vented container may cause explosion. Keep surrounding containers cool with water spray.  
  
Stability: Stable.  
Conditions to Avoid: Contact with open flame.  
Hazardous Decomposition Products: Carbon Monoxide and unidentified organic compounds may be formed during combustion.  
Hazardous Polymerization: Will not occur.

## **SECTION VI: ACCIDENTAL RELEASE MEASURES**

### **STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

Dike area. Remove all sources of ignition. Ventilate area if necessary. Absorb free liquid with earth, sand, clay, or absorbent pads and place in non-leak containers for disposal. Flush area for trace residue and dispose of as below.

### **WASTE DISPOSAL METHOD:**

In accordance with Federal, State, and Local Laws.

---

## **SECTION VII: HANDLING AND STORAGE**

Protect against physical damage. Store in a cool, dry, well-ventilated location away from any area where fire hazards may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid sparks. Storage and use areas should be NO SMOKING areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapor, liquid); observe all warnings listed for the product. Do not attempt to clean empty containers since residue is difficult to remove. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, sparks, flame, static electricity, or other sources of ignition: they may explode and cause injury or death.

---

## **SECTION VIII: SPECIAL PROTECTION INFORMATION**

Respiratory Protection:	Normally not needed in a well-ventilated area.
Ventilation:	Mechanical to maintain good airflow.
Protective Gloves:	Rubber.
Eye Protection:	Goggles or safety glasses.
Other:	As needed to minimize exposure.
Hygienic Practices:	Always wash face and hands after contact.

---

## **SECTION IX: TYPICAL PHYSICAL AND CHEMICAL PROPERTIES**

Flash Point:	64.4 °C or 148 °F ASTM D93
Boiling Point:	Not available
Specific Gravity (H <sub>2</sub> O=1):	0.855 @ 25 °C
Solubility in Water:	nil
Viscosity cps @ 25 °C	Water-like
Appearance & Odor:	Light Straw liquid, petroleum odor

Note: Not all tests are conducted routinely. It is recommended that you conduct your own tests.

---

## **SECTION X: STABILITY AND REACTIVITY**

Stability:	Stable.
Conditions to Avoid:	Contact with open flame.
Hazardous Decomposition Products:	Carbon Monoxide and unidentified organic compounds may be formed during combustion.
Hazardous Polymerization:	Will not occur.

---

## **SECTION XI: TOXICOLOGICAL INFORMATION**

### **SIGNS AND SYMPTOMS OF EXPOSURE:**

Eyes:	Irritation, redness.
Dermal:	Dryness, irritation, redness.
Inhalation:	Vapors may irritate nose, throat, or respiratory tract.
Ingestion:	Nausea, vomiting, dizziness, headache, blurred vision.
Acute Health Hazards:	Irritation of skin and eyes.
Chronic Health Hazards:	Observations in animals include blood, kidney and reproductive effects.

---

## **SECTION XII: ECOLOGICAL INFORMATION**

*No data available at this time.*

---

## **SECTION XIII: DISPOSAL CONSIDERATIONS**

Whatever cannot be saved for recovery and recycling should be handled as hazardous waste and disposed of in accordance with State, Federal, and Local laws.

---

**SECTION XIV: TRANSPORT INFORMATION**

NOTE: Information in this section (Section 14) is presented as a guide only. Requirements may vary depending upon package size and exceptions used, if any. Follow current, applicable requirements under DOT, TDG, IMO/IMDG, ICAO/IATA to ensure regulatory compliance.

**DOT:** UN 1993, Flammable liquids, N.O.S. (petroleum distillates), 3, PG III,  
Non-bulk shipments may be exempted if criteria in 49 CFR 173.150(b)(3) are met.

**CANADIAN TDG:** UN 1993, Flammable liquids, N.O.S. (petroleum distillates), 3, PG III

**IMDG:** UN 1993, Flammable liquids, N.O.S. (petroleum distillates), 3, PG III

**IATA:** UN 1993, Flammable liquids, N.O.S. (petroleum distillates), 3, PG III  
Quantity Limitations: Passenger Aircraft: 60 L Cargo Aircraft: 220 L

---

**SECTION XV: REGULATORY INFORMATION**

This product requires a proposition 65 statement.

---

**SECTION XVI: OTHER INFORMATION**

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in the use of this material.

Issue Date: May 27, 2016  
Revision Date: \_\_\_\_/\_\_\_\_/\_\_\_\_