

## SAFETY DATA SHEET

### SECTION I: IDENTIFICATION

C.A.T. Products, Inc.  
103 Gypsum Rd  
Stroudsburg, PA 18360  
(800) 872-8921  
24 hr. emergency phone ChemTel 1-800-255-3924

*May be used to comply with OSHA's  
Hazard Communication Standard  
29CFR 1910.1200. Standard  
must be consulted for specific  
requirements..*

Trade Name:	75W140 Gear Oil
Product Code:	CP-SL374
U.S. D.O.T. Shipping Name:	Not Applicable
Technical Name:	Not Applicable
U.S. D.O.T. Primary Hazard Class:	Non Regulated
U.S. D.O.T. Secondary Hazard Class:	Not Applicable
Identification Number:	Not Applicable
IATA (Airline)	Non Regulated
Maritime	Non Regulated
Packing Group:	III

Product type & use: Consumer (retail) product, Synthetic Gear Oil

---

### SECTION II: HAZARDS IDENTIFICATION

GHS signal word:	GHS pictogram:	Precautionary statement:
Warning		Keep out of reach of children

---

### SECTION III: COMPOSITION INFORMATION ON INGREDIENTS

Ingredients	cas no	range %
Residual solvent Dewaxed petroleum	64742-62-7	0.05-0.10
Additives	Proprietary	0.005-0.01
Olefin sulfide	Proprietary	0.001-0.005

---

### SECTION IV: FIRST-AID MEASURES

#### *EMERGENCY AND FIRST AID PROCEDURES:*

Eyes:	Flush with large amounts of water for 15 minutes.
Dermal:	Wash with soap and water.
Inhalation:	Remove victim to fresh air.
Ingestion:	Do not induce vomiting. Get medical attention or call poison control.

---

### SECTION V: FIRE-FIGHTING MEASURES

Extinguishing Media:	Dry chemical foam, or water fog.
Special Fire Fighting Procedures:	Protect against decomposition products. Wear Self Contained Breathing Apparatus.
Unusual Fire & Explosion Hazards:	Heating of non-vented container may cause explosion. Keep surrounding containers cool with water spray
Stability:	Stable.
Conditions to Avoid:	Contact with open flame.
Hazardous Decomposition Products:	Carbon Monoxide and unidentified organic compounds may be formed during combustion.
Hazardous Polymerization:	Will not occur.

---

### SECTION VI: ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Dike area. Remove all sources of ignition. Ventilate area if necessary. Absorb free liquid with earth, sand, clay, or absorbent pads and place in non-leak containers for disposal. Flush area for trace residue and dispose of as below.

**WASTE DISPOSAL METHOD:**

In accordance with Federal, State, and Local Laws.

---

**SECTION VII: HANDLING AND STORAGE**

Protect against physical damage. Store in a cool, dry, well-ventilated location away from any area where fire hazards may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid sparks. Storage and use areas should be NO SMOKING areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapor, liquid); observe all warnings listed for the product. Do not attempt to clean empty containers since residue is difficult to remove. DO not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, sparks, flame, static electricity, or other sources of ignition: they may explode and cause injury or death.

---

**SECTION VIII: SPECIAL PROTECTION INFORMATION**

Respiratory Protection:	Normally not needed in a well-ventilated area.
Ventilation:	Mechanical to maintain good airflow.
Protective Gloves:	Rubber.
Eye Protection:	Goggles or safety glasses.
Other:	As needed to minimize exposure.
Hygienic Practices:	Always wash face and hands after contact.

---

**SECTION IX: TYPICAL PHYSICAL AND CHEMICAL PROPERTIES**

Flash Point:	>200 °F ASTM D56 Tag Closed Cup
Boiling Point:	not available
Specific Gravity (H <sub>2</sub> O=1):	0.85 @ 25°C
Solubility in Water:	nil
Viscosity cps @ 25°C	viscous
Appearance & Odor:	clear liquid, petroleum odor

---

Note: Not all tests are conducted routinely. It is recommended that you conduct your own tests.

---

**SECTION X: STABILITY AND REACTIVITY**

Stability:	Stable.
Conditions to Avoid:	Contact with open flame.
Hazardous Decomposition Products:	Carbon Monoxide and unidentified organic compounds may be formed during combustion.
Hazardous Polymerization:	Will not occur.

---

**SECTION XI: TOXICOLOGICAL INFORMATION**

**SIGNS AND SYMPTOMS OF EXPOSURE:**

Eyes:	Irritation, redness.
Dermal:	Dryness, irritation, redness.
Inhalation:	Vapors may irritate nose, throat, or respiratory tract.
Ingestion:	Nausea, vomiting, dizziness, headache, blurred vision.
Acute Health Hazards:	Irritation of skin and eyes.
Chronic Health Hazards:	Observations in animals include blood, kidney and reproductive effects.

---

**SECTION XII: ECOLOGICAL INFORMATION**

*No data not available at this time.*

---

**SECTION XIII: DISPOSAL CONSIDERATIONS**

Whatever cannot be saved for recovery and recycling should be handled as hazardous waste and disposed of in accordance with State, Federal, and Local laws.

---

**SECTION XIV: TRANSPORT INFORMATION**

NOTE: Information in this section (Section 14) is presented as a guide only. Requirements may vary depending upon package size  
CAT 85W140 Gear Oil

and exceptions used, if any. Follow current, applicable requirements under DOT, TDG, IMO/IMDG, ICAO/IATA to ensure regulatory compliance.

**General Transportation Information**

**DOT**

**IMDG**

**IATA**

---

**SECTION XV: REGULATORY INFORMATION**

This product does not require a proposition 65 statement

---

**SECTION XVI: OTHER INFORMATION**

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Vendor assumes no responsibility for injury to vendee or third person proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in the use of this material.

Issue date

May 19, 2015

Revision date:

\_\_\_\_/\_\_\_\_/\_\_\_\_