



F.A.Q. Fresh Air Quality


Cabin Air Cleaning Service - Spray Gun Style

NOTE: Technician should wear safety glasses and a particle mask.



If Replacing the Cabin Air Filter: Follow manufacturer's instructions for removing cabin air filter but DO NOT install new filter until the F.A.Q. service is completed! After removing the filter, proceed to Step 1.

STEP 1: Remove cap & foil seal from bottle of solution. Attach bottle to F.A.Q. Spray Gun and the spray gun to shop air (pressure 100-125 psi).



**Normal A/C
Fan on High**



Fresh Air

STEP 2: Close all windows; remove pets and people from the vehicle and start engine. Set A/C controls to normal on position, fan on high. Set selector to Outside or Fresh Air, close doors.



STEP 3: Under the Hood, locate exterior air intake (usually at base of windshield), aim F.A.Q. Spray Gun at air intake and spray liberally into air intake for 50-60 seconds.



**70° Temp.
Dash Vents Only**



Recirculate

STEP 4: Interior of Vehicle: Set temperature controls to middle position or 70° and set air to blow through dash vents only. Set selector to re-circulate interior air (Max A/C if no separate setting).

STEP 5: Begin on driver's side and fog the floor area, seats, seat belt and ash try (after cleaning). Move to passenger floor and seats. Continue until you have reached the front passenger floor area. After fogging the seats and carpet, lightly fog the headliner. Finish by standing outside of vehicle, while positioning arm and gun inside aiming at the passenger floor area. Continue fogging interior until all cleaning solution is dispensed.



STEP 6: Close doors and allow cleaner to circulate throughout vehicle interior. (Approximately 2-4 minutes total time) When finished, shut off, open all doors to ventilate vehicle.

If you removed the cabin air filter: You can now install the new filter following the manufacturer's instructions.