

The Complete Solution for A/C Oil

A/C Oil Charge Plus is a universal way to service A/C systems. It works in both PAG and POE oils, as well as R134a and R1234yf refrigerants. Unlike other A/C sealants, A/C Oil Charge Plus is an oil based sealant that does not have any of the dangerous side effects. It will not harden, crystallize, clog the A/C system or harm the recovery equipment.

- Permanently seals leaks
- Enhances A/C compressor oil
- Meets SAE J2670 A/C additive standard
- Safe for all A/C systems
- Contains concentrated A/C dye
- **Immediately Lowers Vent Temperatures!**

Since it can safely remain in the A/C system and prevent leaks from occurring in the future, it is an excellent preventive maintenance product. This one product will stop leaks, enhance performance, extend component life and top up refrigerant oil.



FEATURES AND BENEFITS:

1. A/C oil Charge Plus technology effectively finds and permanently stops leaks as they form. Does not harden or crystallize.
2. A/C Oil Charge Plus dye fluoresces leaks brighter than the competition.
3. Friction Modifier increases the lubricity (less friction) of the compressor oil, improving efficiency (friction coefficient) by 50% and thereby improving fuel economy.
4. Anti-wear Additive creates a thin film that reduces contact between metal parts; reducing friction and heat, thereby extending component life. This effectively quiets noisy compressors.
5. Antioxidant stops the oxidation process, reduces acidity and prolongs oil life.



INSTRUCTIONS:

Add Run-Rite A/C Oil Charge Plus after servicing the A/C system or anytime to enhance compressor oil, add UV dye or stop annoying slow A/C leaks.



1. Choose the correct adapter hose (R134a or R1234yf hose) remove cap and connect hose to the threaded fitting at the tube end.



2. Pull the plunger back on the Install Gun and insert tube in gun.



3. With engine off, locate the Low Pressure A/C port and connect the hose fitting to the port.



4. Squeeze the trigger on the Install Gun until all of the A/C Oil Charge Plus is dispensed into the system. Remove the hose and replace the cap on the Low Pressure fitting. Start vehicle and set A/C to Max and run compressor for 3-5 minutes to complete service