



Product Data Sheet #6404

DOT 4 Brake Fluid Super Heavy Duty

High Performance Brake Fluid

DOT 4 Motor Vehicle Brake Fluid exceeds SAE Spec J1704, federal Spec W-B680A and conforms to Federal Motor Vehicle Standard 116 and ISO 4925.

Brake-Rite DOT 4 Super Heavy Duty Brake Fluid:

For use in all types of automotive brake systems recommending a DOT 3 or DOT 4 fluid. Can be mixed with all approved DOT 3 and DOT 4 fluids.

DIRECTIONS:

Follow vehicle manufacturers recommendations when adding brake fluid. Keep brake fluid clean and dry. Contamination with dirt, water, petroleum products and other material may result in brake failure or other costly repairs. Clean all dirt from cylinder and surrounding area before removing cap.

CAUTION: Store brake fluid only in its original container. Keep container clean and tightly closed to prevent absorption of moisture. **DO NOT REFILL CONTAINER AND DO NOT USE FOR OTHER LIQUIDS.** Avoid spilling fluid on car finish or brake lining. Minimum wet boiling point is 311°F. Keep out of reach of children. Avoid contact with eyes. In case of contact flush thoroughly with for a prolonged period and call a physician. Contains a proprietary mixture of glycol ethers, polyglycols, oxidation inhibitor and corrosion inhibitors.

PROPERTIES	Run-Rite DOT 4 Brake Fluid	Requirements
PRODUCT PROPERTIES		
Boiling Point, minimum (°F)		
Reflux	480	446
Wet reflux	330	311
Flashpoint COC (°F)	274	
pH	8.1 - 9.6	7.0 - 11.5
Specific Gravity @ 15.6°C	1.064 - 1.070	
Viscosity (cst)		
@ -40°C, range	1050 - 1200	1800
@ 100°C, minimum	1.5	1.5
Density @ 15.6° C (lb/gal)	8.91	

*** Typical properties based on fluid tests immediately following manufacture